



March 19, 2024

**REACH (EG Nr.1907/2006)
Statement**

W+P PRODUCTS GmbH confirms operating acc. to the regulation REACH (EG Nr.1907/2006).

All goods, products and packaging that we deliver are articles according to the REACH regulation. According to Article 31 REACH, the creation of a safety data sheet (SDS) for products/articles is not allowed.

For our product groups of **D-Subs, Precision-Female Headers, IC sockets/IC headers and Screws, Bolts**, we identify leaded copper alloy in concentrations > 0,1% (w/w) according the present SVHC 240 candidate list:

| Substance | CAS | List | Remark |
|-----------|-----------|------|--------------------------------------|
| Lead | 7439-92-1 | SVHC | As copper alloy ingredient <= 4 % |

In attachment, please find a table with the concerned W+P series with the named SVHC component and the SCIP-Number.

Solid lead metal, e.g. as a component of the copper alloy, is considered toxic for reproduction if the concentration limit of 0.3% by mass are exceeded. The classification of lead as toxic to reproduction does not mean that there is an immediate danger from materials containing lead. The potentially toxic properties of lead as a chemical element have also been known for years and are taken into account accordingly, e.g. in special occupational health and safety legislation.

The referred products are no compound or preparation according to CLP/GHS and they are not subject to labeling or rating obligations.

Generally, lead continues to be an important element for copper alloys for improved milling capabilities. Until now, it has been difficult to substitute lead. Some W+P D-Sub series only exceed the 0.1% limit when using screw options. Ask our sales department about the possibility of a - **LF21**- screw option. This allows the compliant status, related to lead, can be obtained without exceeding the limit.

Based on our supplier obligations to adhere to the REACH regulations, you may expect our products to conform to REACH even when the candidate list has be revised.

If this is exceeded, we will inform you in accordance with the requirements of the REACH regulation.

Peter Schneider
Lead of quality assurance
W+P PRODUCTS GmbH

(This document is valid without signature)

ROHS Exemption 6c/6a ; REACH - Lead (CAS: 7439-92-1) over 0,1% (w/w)
 Lead concentration in W+P PRODUCTS series is max. 4 % for copper alloys (6c) and max. 0,35 % for steel alloys (6a)

Mounting option: Last position on item number: - 0- without mounting / 1-CL: mounting option (if available) Page: 1/3

| W+P Series | SVHC component | SCIP no. | ROHS Exemption |
|-----------------------------|------------------------|--------------------------------------|----------------|
| 100 without mounting option | Contact | 083e9684-169f-42dc-b52e-cd16beb21d50 | 6c |
| 100 with mounting option | Contact, screws, bolts | 31c9f59d-1448-4b12-a02b-e520d54ae934 | 6c |
| W100 | Contact | 29b3f69a-0c0e-4104-a413-bb43a0678ab1 | 6c |
| WA100 | Contact | 29571cc4-54ed-4909-8e82-9bd16d30c842 | 6c |
| 101 without mounting option | Contact | 73bad181-b02b-4a47-949f-eda00e43b758 | 6c |
| 101 with mounting option | Contact, screws, bolts | 058ca9b3-547b-4fd1-baeb-2710a21bab74 | 6c |
| W101 | Contact | 45206902-32aa-45d4-a7a9-205dd9640009 | 6c |
| 102 without mounting option | Contact | 57579932-82f6-4474-8a69-664f59c28120 | 6c |
| 102 with mounting option | Contact, screws, bolts | 0645311b-8569-4ba5-abad-55cf3a3c3a60 | 6c |
| W102 | Contact, screws, bolts | 365c48c4-49a1-483d-ba49-8c47e97130e8 | 6c |
| W109 | Contact, screws, bolts | 66671c3e-8ae0-44d5-b937-6c8669dff2e | 6c |
| W110 | Contact, screws, bolts | 5d68c2ce-63a3-4cc6-819a-6504d95abdf3 | 6c |
| W112 | Contact, screws, bolts | bbef1a35-22d6-45e2-8546-a7caaaff3a27 | 6c |
| WA112 | Contact, screws, bolts | f6638abc-c6a8-4a40-9c29-46ebcfb9fd5f | 6c |
| 153 | Sleeve | 3a6a7a00-d897-4e54-a73f-7753558cf7c6 | 6c |
| 153C | Sleeve | 0612206b-2466-41f3-a375-5d7e10f1f38e | 6c |
| 153PF | Sleeve | 6bf7a44b-56e5-4004-8216-c409a5cfbfe4 | 6c |
| 153PF-38 | Sleeve | edbf7eb4-8b1a-4a13-b6f2-520762609260 | 6c |
| 154 | Sleeve | 9e545ab0-f64f-4be7-a7ae-1cb7e9aa6fce | 6c |
| 155 | Sleeve | b8b27999-532f-485a-810f-d2afcc7dc222 | 6c |
| 155C | Sleeve | 543ef4f0-d210-4502-a0e0-beeb7d220276 | 6c |
| 164 | Contact | 41ef8066-55ee-4f94-a4e2-d73bb362fa3e | 6c |
| 169 | Sleeve | 12eeb31a-c0dd-4d7c-bdb7-dcc9d4d38630 | 6c |
| 169C | Sleeve | 0d46c309-5f74-44a9-84f4-5a62d607827a | 6c |
| 170 | Sleeve | f4ec00b0-d344-4bd3-ba8a-e865be79eebd | 6c |
| 171 | Sleeve | 2339d964-eb96-46e7-83d7-4b0ba8193793 | 6c |
| 172 | Sleeve | 1739b692-42df-4582-b527-8136fea38eec | 6c |
| 174 | Sleeve | b5606044-a828-4c7b-a512-31d37235edd1 | 6c |
| 175 | Contact | 395b8bac-fc22-4449-b62e-8e9f901cfa8e | 6c |
| 176 | Contact | 2bf70b23-5f18-4f7c-88e0-c9a293428bd2 | 6c |
| 178 | Contact | b25a0f21-19db-469f-9232-04b573ecc318 | 6c |
| 181 | Sleeve | 80de7021-82d5-4b8f-9085-08d61155004f | 6c |
| 182 | Sleeve | 513190ef-0ee4-47e4-88ec-62332c8deccf | 6c |
| 182C | Sleeve | 4f006835-3ddd-463e-bc05-8f0ff3202c6a | 6c |
| 182PF | Sleeve | 4cbb2cb9-68c8-4f68-85de-b7520536b612 | 6c |
| 184 | Sleeve | 6f3ee0d6-4a9d-4142-9dd1-3fdc2ca0a8ed | 6c |
| 186 | Sleeve | 678a9640-e6f9-44b4-83ed-6086fe5164a0 | 6c |
| 187 | Sleeve | 41abd3a4-d389-4ea9-ab24-961c4fea99dd | 6c |
| 188 | Contact | e8b26c42-ddf4-4f61-92ef-f3467ce1dca0 | 6c |
| 189 | Contact | 69d66e45-05d5-4bcf-bd49-22309b2120a1 | 6c |
| 191 | Contact | 1ebe3d58-a08b-4a9b-a7c1-0c2c2a3e1272 | 6c |
| 253 | Sleeve | 73155372-5335-4089-a466-8307d38df668 | 6c |
| 253C | Sleeve | 837a335f-6dc5-41b3-8ad3-7e7804539ede | 6c |
| 254 | Sleeve | 89f93134-4613-4d28-ae0f-94d12a01c334 | 6c |
| 255 | Sleeve | b6b27061-871c-494d-9579-8532b1b141f1 | 6c |
| 255C | Sleeve | 7c8b0128-160f-4bbe-843e-cd3aaede3a4f | 6c |
| 256 | Sleeve | 2187661e-138d-4b1d-a0cd-4af7f1dedb11 | 6c |
| 257 | Sleeve | fbdd1cb9-224b-4344-a1f3-0c0b946e83b1 | 6c |

ROHS Exemption 6c/6a ; REACH - Lead (CAS: 7439-92-1) over 0,1% (w/w)
 Lead concentration in W+P PRODUCTS series is max. 4 % for copper alloys (6c) and max. 0,35 % for steel alloys (6a)

Mounting option: Last position on item number: - 0- without mounting / 1-CL: mounting option (if available) Page: 2/3

| W+P Series | SVHC component | SCIP no. | ROHS Exemption |
|-----------------------------|-----------------------------|---------------------------------------|----------------|
| 300 without mounting option | Contact | 4593bb73-59a8-4f81-a5c3-cd7e51f7c55f | 6c |
| 300 with mounting option | Contact, screws, bolts | 07c6e2d2-dfb9-478b-b07a-63844f329dfc | 6c |
| 307 | Screw | 2b94d271-e844-4f50-89ee-0577548fe285 | 6c |
| W307 | Screw | fc3d9f57-b174-4d09-9a88-12a3ccd1e0b2 | 6c |
| 308 | Screw | 0749c251-ee05-427d-8c75-9ee2e793a1ca | 6a |
| 309 | Screw | e58f3ae7-9a01-428d-ba4c-125b5dbe8d50 | 6a |
| 315 | Sleeve | adcee53b-35f2-4a6f-bc3f-c27bc5c73f1a | 6c |
| 322 | Sleeve | 6a11acda-1b75-41a3-9bac-b8b4bfdad5aa4 | 6c |
| 325 | Sleeve | c95f160f-c539-47c9-ba85-fddc278f6c1b | 6c |
| 326 | Sleeve | fd8a2516-e281-4740-81f9-975d357a6b8d | 6c |
| 327 | Sleeve | 4843755a-d32b-40e2-b122-7846ccf5f07a | 6c |
| 330 | Contact | 690a3000-26da-4de4-b0a4-b392420c1f89 | 6c |
| 354 | Screw | 9762b3a5-d556-409f-8c16-10a420c18f66 | 6c |
| 355 | Contact | 3e6cc8cc-bb83-463e-8bd8-c7d124605fb5 | 6c |
| 363 | Screw | 3f332dea-85f3-4e5e-a0e3-f0dcc6a3c459 | 6a |
| 364 | Screw | 19c7b9a2-6429-463b-947e-17e50441f16d | 6a |
| 425 | Contact | 17e6c962-b03d-4014-9774-590f31c00f96 | 6c |
| 636 without mounting option | Contact | 3d7ee03f-781c-4255-b99f-415c3227f015 | 6c |
| 636 with mounting option | Contact, screws, bolts | fa6b675e-92b3-4b3e-80fb-a2261a79ee20 | 6c |
| 637 | Contact | b551f67f-c9f0-4e77-84ff-89577718fe92 | 6c |
| 823 | Contact | 0f322cb7-f1bd-43d9-8629-5e3c28b6cf21 | 6c |
| 854 | Screw | 0306d52c-91b9-47a3-b465-d7809301df42 | 6c |
| 856 | Screw | 45d71f15-e899-41a4-9788-f31d26ff783c | 6c |
| 857 | Screw | ec22f4aa-b99b-4cf1-a213-6ac798eb160d | 6c |
| 858 | Screw | 2586d58b-68e6-4bba-8042-63296c932395 | 6c |
| 881 | Housing and contact | in request | 6c |
| 882 | Housing and contact | in request | 6c |
| W901 | Screw | 3435add6-cda6-405c-b932-53211ec6de4e | 6c |
| 902 without mounting option | Contact | 53a35d8c-b926-4664-a965-215cddbdc0a74 | 6c |
| 902 with mounting option | Contact, screws, bolts | a48f3c4b-9c34-4a6e-bc93-da8e7b50d871 | 6c |
| 905 | Screw | c4860a6e-9ac3-4562-815b-6a1629d54b47 | 6c |
| 906 | Screw | ff2bf6e4-31a8-4c1c-8a78-b480ef7b9f8e | 6c |
| 909 | Screw | f1b5b2fa-2a94-44d9-9e58-ed4378e59fa6 | 6c |
| 963 | Screw | cd006795-b817-4750-9261-2101b97d0f34 | 6c |
| 1531 | Sleeve | cf0988d6-240d-4ef4-9a9e-d4f869c75e66 | 6c |
| 1532 | Sleeve | 85c2e288-9219-4372-9414-e0876edb0c00 | 6c |
| 1533 | Sleeve | 5b6cbcbcb-6262-428f-95d9-126a99432638 | 6c |
| 1534 | Sleeve | 4072eedc-2248-4f62-8d53-fe7b7981d1d6 | 6c |
| 1535 | Sleeve | 53ae8484-c7c5-4f82-bb4c-23114c53c4b3 | 6c |
| 1551 | Sleeve | cc83f4fd-8ec2-4726-9940-9a0abf5a5642 | 6c |
| 1551C | Sleeve | 45de6865-bc51-4abf-aed0-8437371d506f | 6c |
| 1552 | Sleeve | 61c8d6e2-5cee-43fa-a727-b5297ac42822 | 6c |
| 3230 | Sleeve | 61168b31-eb9e-4ed1-bb9a-05df4340b7bb | 6c |
| 3232 | Contact | ec10290c-55e7-413a-b631-d9d82bd42711 | 6c |
| 3233 | Contact | 13766415-f21b-4e95-8dc9-9dc499bcb346 | 6c |
| 3234 | Contact | f78a7ccb-fc96-4246-a88c-fef1a212a033 | 6c |
| 3240 | Sleeve | 93029492-d549-4498-92fa-9088b2f002be | 6c |
| 3242 | Contact | ca18bf73-b42e-4d02-b618-3a7ccc506fb3 | 6c |
| 5251 | Male Contact /Female-sleeve | fd94f24b-3cda-432d-bc50-170bd5524489 | 6c |
| 5252 | Male Contact /Female-sleeve | 9dbb9348-02f3-4efd-ba3c-1654ca39fe38 | 6c |
| 5255 | Male Contact /Female-sleeve | fe972ee9-c21b-4c6b-9bee-b49ccc620fa0 | 6c |
| 5260 | Male Contact /Female-sleeve | bf619da1-cb35-4c43-9a4e-ab7fa08ae747 | 6c |

ROHS Exemption 6c/6a ; REACH - Lead (CAS: 7439-92-1) over 0,1% (w/w)
 Lead concentration in W+P PRODUCTS series is max. 4 % for copper alloys (6c) and max. 0,35 % for steel alloys (6a)

Mounting option: Last position on item number: - 0- without mounting / 1-CL: mounting option (if available) Page: 3/3

| W+P Series | SVHC Component | SCIP No. | Mounting option |
|------------|----------------|---------------------------------------|-----------------|
| 7063 | Contact | eb3c3772-2bcb-4d1a-85ce-1f306d2bd9be | 6c |
| 7090 | Sleeve | 2425d780-9fb9-4a8f-9984-d8750259e619 | 6c |
| 7452 | Sleeve | 7245cdf-f-eaca-4597-bfa9-a8cc5aba718a | 6c |
| 7452C | Sleeve | d05e320e-8981-4d75-8e8d-8e45c52e5687 | 6c |

W+P Series concerned only with mounting options (Screws, Bolts)

ROHS Exemption 6c ; REACH - Lead (CAS: 7439-92-1) over 0,1% (w/w)
 Lead concentration in W+P PRODUCTS series is max. 4 % for copper alloys (6c)

| W+P Series | SVHC Component | SCIP No. | Mounting option |
|---------------------------------|----------------|--------------------------------------|-----------------------------|
| 105 only with mounting option | Screws, bolts | f8bb884e-90a5-479c-a364-89746894ba16 | B1, B2, 1,2,3,4,5,6 |
| 106 only with mounting option | Screws, bolts | f29511f2-5179-4a76-90a1-111d5bade0ee | BL, CL, B1, B2, 1,2,3,4,5,6 |
| 107 only with mounting option | Screws, bolts | 9b702233-f6b4-45fe-ac5b-17c05de72a5d | Bolts -10- ; -20- |
| 108 only with mounting option | Screws, bolts | 53210811-7526-4dae-8899-0a3f0a58e96f | BL, CL, B1, B2, 1,2,3,4,5,6 |
| 109 only with mounting option | Screws, bolts | 2c103ef0-e010-4119-82e3-c934bbbabbcd | BL, CL, B1, B2, 1,2,3,4,5,6 |
| 110 only with mounting option | Screws, bolts | fd68ed9f-344d-4cc0-baeb-dddc3a8ac0d2 | Bolts -10- ; -20- |
| 111 only with mounting option | Screws, bolts | acf1cbc2-c379-46b6-b44f-71d25fff08d1 | Bolts -10- ; -20- |
| 114 only with mounting option | Screws, bolts | 0fd30abb-e800-4453-a28f-1b336b815562 | 10, UNC 4-40 |
| 114-6 only with mounting option | Screws, bolts | e577b362-2073-4cbf-a309-6dc6072fbb6c | 10- UNC 4-40 / -20- M3 |
| 115 only with mounting option | Screws, bolts | 59061ca8-7cf6-494b-9d20-ff485881a03e | BL, CL, B1, B2, 1,2,3,4,5,6 |
| 116 only with mounting option | Screws, bolts | 50831c8d-4c42-4897-8717-b0051ba3dbb7 | BL, CL, B1, B2, 1,2,3,4,5,6 |
| 346 only with mounting option | Screws, bolts | af1d0ae9-1382-4a0f-bb1b-92e302ba7d34 | Bolts -10- ; -20- |
| 347 only with mounting option | Screws, bolts | 05a71703-83b1-4dab-901b-cedef04079b9 | Bolts -10- ; -20- |
| 908 only with mounting option | Screws, bolts | 2f67f213-f8a5-4271-8b23-509d523a094d | Bolts -38- |
| 1141 only with mounting option | Screws, bolts | c7440d99-78d4-41a3-b7ea-a68443cd4173 | - 10 - ; UNC 4-40 |