





On release of the data sheet, previous releases are no longer valid. Dimensions and tolerances are subject to change.



Insulator: Thermoplastic, rated UL94 V-0
 Contact Material: Copper alloy
 Contact Surface: Au over Ni
 Contact Resistance: 20 mΩ max.
 Insulation Resistance: 1000 MΩ min.
 Test Voltage: 500 V AC/DC
 Current Rating: 1.5 A
 Temperature Range: -40 °C ~ +105 °C
 Processing Temperature: 230 °C for 30~60 seconds
 (260 °C for 5 seconds)

Recommended P.C.B Layout (Top Side)
 (PCB BOARD TOLERANCE ± 0.05)



Series 46-317 — **Contacts** 26 — **Type** 20 — **Plating** 00
 04-30 Zweireihig Double row
 20 Gerade Straight
 00 Vergoldet Gold plated

Copying of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the prosecution of the courts. In the event of the grant of a patent or the registration of a utility model or design.




X.X	±0.30
X.XX	±0.20
X.XXX	±0.10
Angle	±3°
DIM	TOL



Serial Number 46-317			
Part Name Pin Header, 2.00mm Pitch, Straight Double Row - 4mm Height			
Creation date 2021-03-22	Drawn AL	Approved PS	Approval date 2021-12-07
REACH (EG) Nr. 1907/2006 RoHS 2011/65/EU compliant		Scale %	Sheet 1/2


On release of the data sheet, previous releases are no longer valid. Dimensions and tolerances are subject to change.

Copying of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the registration of a utility model or design.



Insulator:	Thermoplastic, rated UL94 V-0
Contact Material:	Copper alloy
Contact Surface:	Au over Ni
Contact Resistance:	20 mΩ max.
Insulation Resistance:	1000 MΩ min.
Test Voltage:	500 V AC/DC
Current Rating:	1.5 A
Temperature Range:	-40 °C ~ +105 °C
Processing Temperature:	230 °C for 30~60 seconds (260 °C for 5 seconds)

Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE ±0.05)



Series	Contacts	Type	Plating
46-317	26	21	00
	04-30 Zweireihig Double row	21 Gewinkelt Right-Angled	00 Vergoldet Gold plated

X.X	±0.30
X.XX	±0.20
X.XXX	±0.10
Angle	±3°
DIM	TOL



Serial Number 46-317			
Part Name Pin Header, 2.00mm Pitch, Right-Angled, Double Row - 4mm Height			
Creation date 2021-03-22	Drawn AL	Approved PS	Approval date 2021-12-07
REACH (EG) Nr. 1907/2006 RoHS 2011/65/EU compliant		Scale %	Sheet 2 / 2