




On release of the data sheet, previous releases are no longer valid. Dimensions are subject to change.


Copying of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the registration of a utility model or design.



Insulator	Thermoplastic, UL94 V-0
Contact Material	Brass
Contact Surface	Au over Ni
Contact Resistance	20 mΩ max.
Insulation Resistance	1000 MΩ min.
Test Voltage	500 V AC/DC
Current Rating	1.0 A
Temperature Range	-40 °C ... +105 °C
Processing Temperature	260 °C for 5 seconds



Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE ±0.05)



Series	Contacts *	Dimensions *	Insulator Height	Plating
46-751	040 004-070 Zweireihig Double row	20 20 A=14,30 D=8,45mm 30 A=15,00 D=9,15mm A Customer-specific, max. 35,0mm B/C max. 15,0mm	10 10 H=1,00mm	00 00 Vergoldet Gold plated




X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle	±3°
DIM	TOL



Serial Number 46-751			
Part Name Dual Body Pin Header, 1.27mm Pitch, Double Row			
Creation date 2022-09-06	Drawn AL	Approved PS	Approval date 2022-09-06
REACH (EG) Nr. 1907/2006 RoHS 2011/65/EU compliant		Scale %	Sheet 1/2


On release of the data sheet, previous releases are no longer valid. Dimensions and tolerances are subject to change.

Copying of this document, and giving it to others and the use or communication of the contents thereof, are forbidden without express authority. Offenders are liable to the prosecution of the courts. In the event of the grant of a patent or the registration of a utility model or design.



Insulator	Thermoplastic, UL94 V-0
Contact Material	Brass
Contact Surface	Au over Ni
Contact Resistance	20 mΩ max.
Insulation Resistance	1000 MΩ min.
Test Voltage	500 V AC/DC
Current Rating	1.0 A
Temperature Range	-40 °C ... +105 °C
Processing Temperature	260 °C for 5 seconds

Recommended P.C.B Layout (Top Side)
(PCB BOARD TOLERANCE ±0.05)



Series	Contacts *	Dimensions *	Insulator Height	Plating
46-751	040 004-070 Zweireihig Double row	20 20 A=14,30 D=8,45mm 30 A=15,00 D=9,15mm A Customer-specific, max. 35,0mm B/C max. 15,0mm	15 15 H=1,50mm	00 00 Vergoldet Gold plated

X.X	±0.40
X.XX	±0.25
X.XXX	±0.15
Angle	±3°
DIM	TOL



Serial Number 46-751			
Part Name Dual Body Pin Header, 1.27mm Pitch, Double Row			
Creation date 2022-09-06	Drawn AL	Approved PS	Approval date 2022-09-06
REACH (EG) Nr. 1907/2006 RoHS 2011/65/EU compliant		Scale %	Sheet 2/2