





On release of the data sheet,
previous releases are no longer valid.
Dimensions and tolerances
are subject to change.

Copying of this document, and giving it to others and the use or communication of
the contents thereof, are forbidden without express authority. Offenders are liable to
prosecution and damages. The patent office has been notified of the grant of a patent
or the registration of a utility model or design.



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Insulator	Thermoplastic, rated UL94 V-0
Contact Material	Copper alloy
Contact Surface	Au over Ni
Contact Resistance	20 mΩ max.
Insulation Resistance	1000 MΩ min.
Test Voltage	1000 V AC/DC
Current Rating	3.0 A
Temperature Range	-40 °C ... +105 °C
Processing Temperature	230 °C for 30-60 seconds (260 °C for 10 seconds)

Series

46-923

Dimensions *

14

- 12 B=3.50 C=3.30mm
- 13 B=4.80 C=3.30mm
- 14 B=6.10 C=3.30mm
- 15 B=6.90 C=3.30mm
- 16 B=9.90 C=3.30mm
- 17 B=12.00 C=3.30mm
- 18 B=13.80 C=3.30mm
- 19 B=15.00 C=3.30mm
- 20 B=17.10 C=3.30mm

Weitere Stiftlängen auf Anfrage
More pin length options on request

Contacts *

006

001-020 Einreihig
Single row

Plating

00

00 Vergoldet
Gold plated




X.X	±0.30
X.XX	±0.20
X.XXX	±0.10
Angle	±3°
DIM	TOL



Serial Number 46-923			
Part Name Pin Header, 2.54mm Pitch, Right-Angled, Single Row – 1.5mm Body			
Creation date 2022-02-23	Drawn AL	Approved PS	Approval date 2022-02-23
REACH (EG) Nr. 1907/2006 RoHS 2011/65/EU compliant		Scale %	Sheet


On release of the data sheet,
previous releases are no longer valid.
Dimensions and tolerances
are subject to change.

Copying of this document, and giving it to others and the use or communication of
the contents thereof, are forbidden without express authority. Offenders are liable to
prosecution and damages in the event of the grant of a patent
or the registration of a utility model or design.




Insulator	Thermoplastic, rated UL94 V-0
Contact Material	Copper alloy
Contact Surface	Au over Ni
Contact Resistance	20 mΩ max.
Insulation Resistance	1000 MΩ min.
Test Voltage	1000 V AC/DC
Current Rating	3.0 A
Temperature Range	-40 °C ... +105 °C
Processing Temperature	230 °C for 30-60 seconds (260 °C for 10 seconds)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE ± 0.05)



Series	Dimensions *	Contacts *	Plating
46-924	16	020	00
	12 B=3.50 C=3.30mm	004-040 Zweireihig	00 Vergoldet
	13 B=4.80 C=3.30mm	Double row	Gold plated
	14 B=6.10 C=3.30mm		
	15 B=6.90 C=3.30mm		
	16 B=9.90 C=3.30mm		
	17 B=12.00 C=3.30mm		
	18 B=13.80 C=3.30mm		
	19 B=15.00 C=3.30mm		
	20 B=17.10 C=3.30mm		

Weitere Stiftlängen auf Anfrage
More pin length options on request

X.X	±0.30	WE CONNECT IT			
X.XX	±0.20				
X.XXX	±0.10	Serial Number 46-924			
Angle	±3°	Part Name Pin Header, 2.54mm Pitch, Right-Angled, Double Row – 1.5mm Body			
DIM	TOL	Creation date 2022-02-23	Drawn AL	Approved PS	Approval date 2022-02-23
		 REACH (EG) Nr. 1907/2006 RoHS 2011/65/EU compliant		Scale %	Sheet