





On release of the data sheet,
previous releases are no longer valid.
Dimensions and tolerances
are subject to change.

Copying of this document, and giving it to others and the use or communication of
the contents thereof, are forbidden without express authority. Offenders are liable to
prosecution and damages. The patent office has been notified of the grant of a patent
or the registration of a utility model or design.



Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Insulator	Thermoplastic, rated UL94 V-0
Contact Material	Copper alloy
Contact Surface	Au over Ni
Contact Resistance	20 mΩ max.
Insulation Resistance	1000 MΩ min.
Test Voltage	1000 V AC/DC
Current Rating	3.0 A
Temperature Range	-40 °C ... +105 °C
Processing Temperature	230 °C for 30-60 seconds (260 °C for 10 seconds)




Series	Dimensions *	Contacts *	Plating
46-933	15	010	00
	12 B=3.50 C=3.30mm	001-020 Einreihig	00 Vergoldet
	13 B=4.80 C=3.30mm	Single row	Gold plated
	14 B=6.10 C=3.30mm		
	15 B=6.90 C=3.30mm		
	16 B=9.90 C=3.30mm		
	17 B=12.00 C=3.30mm		
	18 B=13.80 C=3.30mm		
	19 B=15.00 C=3.30mm		
	20 B=17.10 C=3.30mm		

Weitere Stiftlängen auf Anfrage
More pin length options on request

X.X	±0.30	Serial Number 46-933			
X.XX	±0.20	Part Name Pin Header, 2.54mm Pitch, Right-Angled, Single Row – 1.7mm Body			
X.XXX	±0.10	Creation date 2022-02-23	Drawn AL	Approved PS	Approval date 2022-02-23
Angle	±3°	REACH (EG) Nr. 1907/2006 RoHS 2011/65/EU compliant			
DIM	TOL	Scale %			
 WE CONNECT IT®		Sheet			


On release of the data sheet,
previous releases are no longer valid.
Dimensions and tolerances
are subject to change.

Copying of this document, and giving it to others and the use or communication of
the contents thereof, are forbidden without express authority. Offenders are liable to
prosecution and damages. In the event of the grant of a patent
or the registration of a utility model or design.



Insulator	Thermoplastic, rated UL94 V-0
Contact Material	Copper alloy
Contact Surface	Au over Ni
Contact Resistance	20 mΩ max.
Insulation Resistance	1000 MΩ min.
Test Voltage	1000 V AC/DC
Current Rating	3.0 A
Temperature Range	-40 °C ... +105 °C
Processing Temperature	230 °C for 30-60 seconds (260 °C for 10 seconds)

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)



Series	Dimensions *	Contacts *	Plating
46-934	13	022	00
	12 B=3.50 C=3.30mm	004-060 Zweireihig	00 Vergoldet
	13 B=4.80 C=3.30mm	Double row	Gold plated
	14 B=6.10 C=3.30mm		
	15 B=6.90 C=3.30mm		
	16 B=9.90 C=3.30mm		
	17 B=12.00 C=3.30mm		
	18 B=13.80 C=3.30mm		
	19 B=15.00 C=3.30mm		
	20 B=17.10 C=3.30mm		

Weitere Stiftlängen auf Anfrage
More pin length options on request

X.X	±0.30	 WE CONNECT IT	Serial Number 46-934			
X.XX	±0.20		Part Name Pin Header, 2.54mm Pitch, Right-Angled, Double Row – 1.7mm Body			
X.XXX	±0.10		Creation date 2022-02-23			
Angle	±3°		Drawn AL	Approved PS	Approval date 2022-02-23	
DIM	TOL		 REACH (EG) Nr. 1907/2006 RoHS 2011/65/EU compliant		Scale %	Sheet