

Leiterplattenklemme RM 5,00mm, mit Schraubanschluss und Drahtschutz PCB Terminal Block 5.00mm Pitch, With Screw Connection and Wire Guard

Technische Daten / Technical Data

Isolierkörper	Thermoplast, nach UL94 V-0
Insulator	Thermoplastic, rated UL94 V-0
Kontaktmaterial	Messing, verzinkt
Contact Material	Brass, tin plated
Aderquerschnitt	Wire Guard: Stainless Steel
Applicable wire Gauge	AWG 22 ~ 14 (Abisolierung 6-7mm)
RoHS-Ausnahmen 6a-I / 6c	AWG 22 ~ 14 (Wire strip length 6-7mm)
RoHS Exemptions 6a-I / 6c	6c
Durchgangswiderstand	20 mΩ max.
Contact Resistance	20 mΩ max.
Isolationswiderstand	5000 MΩ min.
Insulation Resistance	5000 MΩ min.
Spannungsfestigkeit	1600 V AC
Test Voltage	1600 V AC
Nennspannung	300 V
Voltage Rating	300 V
Nennstrom	15 A
Current Rating	15 A
Temperaturbereich	-40 °C ... +105 °C
Temperature Range	-40 °C ... +105 °C
Verarbeitung	Schraubanschluss, Schraube Stahl M2,6, galvanisiert
	Anzugsdrehmoment: 0,3 Nm max.
	Wellenlöten: 245 °C±10 °C / 5 sec.
Processing	Screw Connection, Screw steel M2.6, galvanized
	Tightening torque: 0.3 Nm max.
	Wave soldering: 245 °C±10 °C / 5 sec.

